Cryptography

Cunsheng Ding, HKUST

COMP3631

Lecture 19: Public Key Infrastructures

Main Topics of This Lecture

1. Two key management issues of public-key ciphers
2. Digital certificates
3. Certificate authorities (CAs)
4. Public key infrastructures (PKIs)

Part I: Key Management Problems of Public-Key Ciphers

Two Key Management Problems of Public-Key Ciphers

Two applications of public-key ciphers:

- The digital envelope key distribution protocol covered in Lecture 14.
- They digital signature scheme using a public-key cipher covered in Lecture 16.

Two key management questions:

- I sent that job offer and my digital signature together to you last week. What will happen if I now say that is not my digital signature?
  - I may claim that the public key you used for signature verification last weak is not my public key.
  - I may claim that someone else shares my key pair.
- How should I publish my public key?

Part II: Digital Certificates

What is a Digital Certificate?

Definition: A digital certificate is an electronic document issued and digitally signed by a "certification authority" that authenticates the identity of its holder.

- It can protect data exchanged online if a public-key is included.
- It should not be forged.

Real world example: passport

A Classification of Digital Certificates

- Server certificates, and
- personal certificates (e.g., containing a public key), also called client certificates.

Question: Any standard on the format of digital certificates?

Answer: Yes, X.509v1 certificate, X.509v2 certificate, X.509v3 certificate.

The X.509v3 Certificate

Signature algorithm identifier: The identifier of the algorithm used to sign the certificate by the issuer. This information is repeated in the Signature field at the end of the certificate.

Issuer and subject name: X.500 Distinguished Name (DN)

- Comprised of multiple Relative DNs (RDNs)
- C = country, ST = state, L = locale, O = organiz.
- OU = organization unit, CN = common name

Subject's public key information: Public key of the subject, plus the identifier of the algorithm for which this key is to be used, together with any associated parameters.

The X.509v3 Certificate

Issuer unique identifier: An optional bit string field used to identify uniquely the issuing CA in the event the X.500 name has been used for different entities.

Subject unique identifier: An optional bit string field used to identify uniquely the subject in the event the X.500 name has been used for different entities.

Extensions: A key usage extension defines for which applications and under which policies a certificated public key can be used.

For example: Digital signature for nonrepudiation, key encryption for key distribution, CA signature verification on certificates (i.e., the holder is a CA), CA signature verification on CRL (i.e., the holder is a CA).

Remark: CRL: Certificate Revocation List (to be introduced later).

- Version Number
- Serial Number
- Signature Algorithm ID
- Issuer Name
- Validity period
  - Not Before
  - Not After
- Subject name
- Subject Public Key Info
  - Public Key Algorithm
  - Subject Public Key
- Issuer Unique Identifier (optional)
- Subject Unique Identifier (optional)
- Extensions (optional)
- Certificate Signature Algorithm
- Certificate Signature

Sample X.509 Certificates

```
Version: 3 (0x2)
Serial Number: 1 (0x1)
Signature Algorithm: md5WithRSAEncryption
Issuer: C=ZA, ST=Western Cape, L=Cape Town, O=Thawte Consulting cc,
        OU=Certification Services Division,
        CN=Thawte Server CA/emailAddress=server-certs@thawte.com
Validity
    Not Before: Aug  1 00:00:00 1996 GMT
    Not After : Dec 31 23:59:59 2020 GMT
Subject: C=ZA, ST=Western Cape, L=Cape Town, O=Thawte Consulting cc,
         OU=Certification Services Division,
         CN=Thawte Server CA/emailAddress=server-certs@thawte.com
Subject Public Key Info:
```

```
Public Key Algorithm: rsaEncryption
RSA Public Key: (1024 bit)
    Modulus (1024 bit):
        00:d3:a4:50:6e:c8:ff:56:6b:e6:cf:5d:b6:ea:0c:
        68:75:47:a2:aa:c2:da:84:25:fc:a8:f4:47:51:da:
        85:b5:20:74:94:86:1e:0f:75:c9:e9:08:61:f5:06:
        6d:30:6e:15:19:02:e9:52:c0:62:db:4d:99:9e:e2:
        6a:0c:44:38:cd:fe:be:e3:64:09:70:c5:fe:b1:6b:
        29:b6:2f:49:c8:3b:d4:27:04:25:10:97:2f:e7:90:
        6d:c0:28:42:99:d7:4c:43:de:c3:f5:21:6d:54:9f:
        5d:c3:58:e1:c0:e4:d9:5b:b0:b8:dc:b4:7b:df:36:
        3a:c2:b5:66:22:12:d6:87:0d
    Exponent: 65537 (0x10001)
X509v3 extensions:
    X509v3 Basic Constraints: critical
       CA:TRUE
```

```
Signature Algorithm: md5WithRSAEncryption
      07:fa:4c:69:5c:fb:95:cc:46:ee:85:83:4d:21:30:8e:ca:d9:
      a8:6f:49:1a:e6:da:51:e3:60:70:6c:84:61:11:a1:1a:c8:48:
      3e:59:43:7d:4f:95:3d:a1:8b:b7:0b:62:98:7a:75:8a:dd:88:
      4e:4e:9e:40:db:a8:cc:32:74:b9:6f:0d:c6:e3:b3:44:0b:d9:
      8a:6f:9a:29:9b:99:18:28:3b:d1:e3:40:28:9a:5a:3c:d5:b5:
      e7:20:1b:8b:ca:a4:ab:8d:e9:51:d9:e2:4c:2c:59:a9:da:b9:
      b2:75:1b:f6:42:f2:ef:c7:f2:18:f9:89:bc:a3:ff:8a:23:2e:
      70:47
```

This is an example of a self-signed certificate. There's no way to verify this certificate except by checking it against itself; instead, these top-level certificates are manually stored by web browsers. Thawte is one of the root certificate authorities recognized by both Microsoft and Netscape. This certificate comes with the web browser and is trusted by default.

Certificate Revocation List

- Signature Algorithm Identifier
- Issuer Name
- This update date
- Next update date
- ……
- User Certificate Serial Number + Revocation date
- ……
- User Certificate Serial Number + Revocation date
- Signature Algorithms and Parameters
- Signature on the CRL

More Information on X.509 Digital Certificates

- Go to: https://en.wikipedia.org/wiki/X.509

Part III: Certificate Authorities

Certificate Authority

(1) It is a trusted third-party.

It is responsible for verifying the identities of cryptographic key holders.

(2) It issues digital certificates.

Asserts that a public key is part of a key-pair held by an individual, organization, or other entity.

(3) It publishes policy detailed in a Certification Practices Statement (CPS).

Part IV: Public Key Infrastructures

Definition of PKI

Definition: A PKI is composed of standards and services that facilitate the use of public-key cryptography and X.509 version 3 certificates in a networked environment.

Remark: There are slightly different definitions. This is similar to **education infrastructures**.

Elements of a Public Key Infrastructure

- Certificate Authorities (CAs): e.g., OpenSSL, Netscape, Verisign, Entrust, RSA Keon
- Public/Private Key Pairs - key management
- X.509 Certificates - certificate management
- LDAP servers (LDAP: Lightweight Directory Access Protocol)
- Certification Practice Statements (issued by a Certificate Authority (CA) to specify the practices and standards that the Certificate Authority (CA) employs in issuing certificates.)


Issues

- Scalability: How many certificates can one CA manage?
- Administration: How to revoke already issued certificates?
- Trust:
  Why should I trust your CA?

Issues: PKI Scalability

- A large PKI requires distributed CAs
  - Local, Reginal, National CAs
  - International CAs
- Certificate Hierarchy
  - Intermediate CA certificates are signed by the CA one-step up.
  - End-user certificates are part of a certificate chain.

Certificate Hierarchy



Verifying Certificate Chains

- Entity accepting certificates must be able to verify CA in the chain.
  - Should the entire chain be present during a handshake?
- Certificate types
  - CA certificates ("Basic Constraints" indicate whether the certificate belongs to a CA)
  - End-user certificates, which cannot be used to issue digital certificates.
- Must distinguish types of certificates. Otherwise, end-users could sign bogus certificates.
- X.509v3 extensions indicate usages of a certificate.

Methods of Publishing Digital Certificates

Without a 3rd party: Own web page, via FTP file

With a 3rd party: Dedicated key server, directory

Why Digital Certificates on Server?

- Encrypt data for someone without prior contact.
- You do not have to store all keys yourself.
- Easier distribution of new keys and updates.

Directory as Key Server

Definition: In computing, a directory is a file system cataloging structure that contains references to other computer files, and possibly other directories.

Why directory as key server?

- As a publishing medium for public keys and certificates.
- Users can put their public key certificate there.
- CAs may put their certificates there.
- The directory documents revocation of keys and/or certificates in the CRL.
- It documents status of a certificate at specific time.